

# All Purpose Vehicle

**Model HAPV (4,000 lb to 5,000 lb Drawbar pull)  
(17.8 kN to 22.2 kN)**



## Standard Features

- F-N-R shifter
- Keyless anti-restart ignition switch
- Two Headlights (recessed)
- Modular lighting includes: Tail/Stop Lights, Backup Light & Turn Signals
- Volt Meter
- Water Temperature Gauge
- Engine Oil Pressure Gauge
- Engine Hour Meter Gauge
- Fuel Level Gauge
- Standard driver and passenger seat

27 Stanley Road \* Kansas City, Kansas 66115 \* USA

913-342-5650 \* 800-255-4262 \* Fax 913-321-5802

[sales@harlan-corp.com](mailto:sales@harlan-corp.com)

[www.harlan-corp.com](http://www.harlan-corp.com)

**Specifications For Model: ALL PURPOSE VEHICLE 4,000 lb (17.8 kN) to 5,000 lb (22.2 kN) DBP**

MODEL	HAPV <sub>40</sub>	HAPV <sub>50</sub>
DBP	4000 lbs (17.8 kN)	5000 lbs (22.2 kN)
Approx. GVW	6670 lbs (3025 kg)	8320 lbs (3774 kg)
Towed weight +/-	40000 lbs (18,140 kg)	50000 lbs (22680 kg)

**Dimensions**

Length	172" (4369 mm)
Width	55" (1397 mm)
Height	61" (1549 mm)
Height with cab	81" (2070 mm)
Bed Size length Optional	72" (1829 mm) 96" (2438 mm)
Wheel Base	106" (2692 mm)
Ground Clearance	6" (152 mm)

**Chassis**

Drive Axle	Heavy-duty Harlan – 8200lb (3719 kg) load capacity
Steer Axle	Heavy-duty Harlan with 1 1/8" king pin
Suspension	Shocks and Leaf Springs on front and rear axles
Towing Coupler	Available upon request
Tires	Front: 6.50 x 10 Rear: LT215/85R x 16
Payload	5000 lbs (2268 kg)
Turning Radius	175" (4445 mm)

**Engine Options**

Manufacturer - Diesel	Cummins, Perkins
Manufacturer – Gasoline/LPG	GM, Zenith, Ford

**Travel/Performance**

Transmission	C-6 Automatic – 3 speeds forward 1 reverse (remanufactured)
Electrical	12 V Negative Ground
Cooling System	Liquid cooled dual cross-flow radiator with trans-cooler
Steering System	Power assist
Service Brakes	Dual Split System, Hydraulic/Hydraulic, dual rear disc w/optional front brakes
Park Brake	Mechanical Drum – lever activated