

Classic Cargomaster

Model HTA (8,000 lb to 10,000 lb) Drawbar pull
(35.59kN to 44.48kN)



Shown with options

Standard Features

- F-N-R shifter
- Keyless anti-restart ignition switch
- Two Headlights
- Combination Tail/Stop Lights & Back-up Light
- Volt Meter
- Water Temperature Gauge
- Engine Oil Pressure Gauge
- Engine Hour Meter Gauge
- Fuel Level Gauge
- Standard driver and passenger seat

27 Stanley Road * Kansas City, Kansas 66115 * USA

913-342-5650 * 800-255-4262 * Fax 913-321-5802

sales@harlan-corp.com

www.harlan-corp.com

MODEL	HTA80	HTA100
DBP	8000 lbs (35.59 kN)	10000 lbs (44.48 kN)
Approx. GVW	9700 lbs (4400 kg)	11500lbs (5216 kg)
Towed weight +/-	80000 lbs (36290 kg)	100000 lbs (45360 kg)

Dimensions

Length	112" (2845 mm)
Width	65.5" (1664 mm)
Height	63" (1600 mm)
Height with cab	84" (2134 mm)
Wheel Base	70" (1778 mm)
Ground Clearance	8" (203 mm)
Turning Radius	120" (3048 mm)

Chassis

Drive Axle	Heavy-duty Harlan – 8200lb (3719 kg) load capacity
Steer Axle	Heavy-duty Harlan with 1 1/8" king pin
Suspension	Leaf Springs on front and rear axles
Towing Coupler	Three-tier hitch with 1 3/4" pin
Tires	Front: 6.50 x 10 Dual Rear: LT215/85R x 16

Engine Options

Manufacturer - Diesel	Cummins, Perkins
Manufacturer - Gasoline	Ford 300 – remanufactured to new (restrictions apply)

Travel/Performance

Transmission	C-6 Automatic – 3 speeds forward 1 reverse (remanufactured by an authorized re-builder)
Optional	545 Automatic – 4 speeds forward 1 reverse (remanufactured by an authorized re-builder)
Electrical	12 V Negative Ground
Cooling System	Liquid cooled radiator with integral transmission cooler
Steering System	Power assist
Service Brakes	Dual Split System, Hydraulic/Hydraulic, dual rear disc w/optional front brakes
Park Brake	Mechanical Drum – lever activated