

# Streamline

**Model HTLP (4,000 lb to 6,000 lb Drawbar pull)  
(17.8 kN to 26.7 kN)**



## Standard Features

- F-N-R shifter
- Keyless anti-restart ignition switch
- Two Headlights (recessed)
- Modular lighting includes: Tail/Stop Lights, Backup Light & Turn Signals
- Volt Meter
- Water Temperature Gauge
- Engine Oil Pressure Gauge
- Engine Hour Meter Gauge
- Fuel Level Gauge
- Standard driver and passenger seat
- Driver Hitch Release

27 Stanley Road \* Kansas City, Kansas 66115 \* USA

913-342-5650 \* 800-255-4262 \* Fax 913-321-5802

[sales@harlan-corp.com](mailto:sales@harlan-corp.com)

[www.harlan-corp.com](http://www.harlan-corp.com)

## Specifications For Model: STREAMLINE 4,000 lb (17.8 kN) to 6,000 lb (26.7 kN) DBP

MODEL	HTLP40	HTLP50	HTLP60
DBP	4000 lbs (17.8 kN)	5000 lbs (22.2 kN)	6000 lbs (26.7 kN)
Approx. GVW	5250 lbs (2381 kg)	6250 lbs (2835 kg)	7250 lbs (3289 kg)
Towed weight +/-	40000 lbs (18,140 kg)	50000 lbs (22680 kg)	60000 lbs (27220 kg)

### Dimensions

Length	114" (2845 mm)
Width	55" (1397 mm)
Height	61" (1549 mm)
Height with cab	81" (2070 mm)
Wheel Base	70" (1778 mm)
Ground Clearance	6" (152 mm)
Turning Radius	120" (3048 mm)

### Chassis

Drive Axle	Heavy-duty Harlan – 8200lb (3719 kg) load capacity
Steer Axle	Heavy-duty Harlan with 1 1/8" king pin
Suspension	Shocks and Leaf Springs on front and rear axles
Towing Coupler	Three-tier hitch Front and Rear with 1 3/4" pin
Tires	Front: 6.50 x 10 Rear: LT215/85R x 16

### Engine Options

Manufacturer - Diesel	Deutz, Cummins, Perkins
Manufacturer – Gasoline/LPG	GM, Zenith, Ford

### Travel/Performance

Transmission	C-6 Automatic – 3 speeds forward 1 reverse (remanufactured)
Electrical	12 V Negative Ground
Cooling System	Liquid cooled dual cross-flow radiator with trans-cooler
Steering System	Power assist
Service Brakes	Dual Split System, Hydraulic/Hydraulic, dual rear disc w/optional front brakes
Park Brake	Mechanical Drum – lever activated