

Hercules

**Model HTA (14,000 lb to 20,000 lb) Drawbar pull
(62.28 kN to 88.96kN)**



Standard Features

- R-N-D-3-2-1 shifter
- Keyless anti-restart ignition switch
- Two Headlights (recessed)
- Modular lighting includes: Tail/Stop Lights, Backup Light & Turn Signals
- Volt Meter
- Water Temperature Gauge
- Engine Oil Pressure Gauge
- Engine Hour Meter Gauge
- Fuel Level Gauge
- Suspension Style driver and passenger seat

27 Stanley Road * Kansas City, Kansas 66115 * USA

913-342-5650 * 800-255-4262 * Fax 913-321-5802

sales@harlan-corp.com

www.harlan-corp.com

Specifications For Model: Hercules 14,000 lb (62.28 kN) to 20,000 lb (88.96 kN) DBP

MODEL	HTWQSB140	HTWQSB160	HTWQSB180	HTWQSB200
DBP	14000 lbs (62.28 kN)	16000 lbs (71.17kN)	18000 lbs (80.07 kN)	20000 lbs (88.96 kN)
Approx. GVW	16800 lbs (7620 kg)	19200 lbs (8709kg)	21600 lbs (9798 kg)	24000 lbs (10890 kg)
Towed weight +/-	140000 lbs (63500 kg)	160000 lbs (72570 kg)	180000 lbs (81650 kg)	200000 lbs (90720kg)

Dimensions

Length	127" (3226 mm)
Width	75" (1905 mm)
Height	69" (1753 mm)
Height with cab	96" (2439 mm)
Wheel Base	77" (1956 mm)
Ground Clearance	10.5" (266.7 mm)
Turning Radius	160" (4064 mm)

Chassis

Drive Axle	Dana Spicer - 20,000lb (9072kg) load capacity
Steer Axle	Heavy-duty Harlan - 7000lb (3175 kg) load capacity
Suspension	Front leaf springs, solid rear mount
Towing Coupler	Front and rear mount Three-tier hitch with 1 3/4" pin
Tires	Front: 8.75 x R16.5 Dual Rear: 8.25 x R15

Engine Options

Manufacturer - Diesel	Cummins Turbo-Charged QSB4.5
-----------------------	------------------------------

Travel/Performance

Transmission	545 Automatic – 4 speeds forward 1 reverse (remanufactured by an authorized re-builder)
Electrical	12 V Negative Ground
Cooling System	10 gal (37.85 liter) capacity with surge tank and integral charge air cooler and transmission cooler
Steering System	Hydrostatic power steering
Service Brakes	Dual Split System, Hydraulic/Hydraulic, front disc and rear drum
Park Brake	Mechanical Drum – lever activated

Specifications subject to improvement and/or change without notice